
Notes to Specifier:

Please visit dassoXTR.com for the most current version of Specifications.

The following product specification language is to assist design professionals in specifying Fused Bamboo in the 3-PART SPECIFICATIONS FOR SIDING.

Sample language is provided for applicable articles in PART 1-GENERAL and Part 2-PRODUCTS following the construction specification institute's section format. Due to variation in specification systems in use, article and paragraph numbers and titles may differ somewhat than presented herein. The sample language should be edited accordingly to fit each firm's specifications.

Articles and paragraphs of this product specification assume the project manual will contain complete Division of 1 documents including 01 25 13-Product substitution procedures, Sections 01 33 00-Submittal Procedures, 01 62 00-Product Options, 01 66 00 Product Storage and Handling Requirements, 01 74 00-Cleaning and Waste Management, 01 77 00-Closeout Procedures, and 01 78 00-Closeout Submittals. Close coordination with Division 1 Sections is Required if the project manual does not contain these sections, additional information may be included under the appropriate articles.

Notes to the specifier are in all Italic text and are contained within rows of asterisks.

Green Text in Italic are Notes Related to LEED® Projects and can be deleted if the project is not intended to attain LEED® Certification

Section 06 46 29
Soffit, Deck Skirting and Wainscoting Board

PART 1 - GENERAL

1.1 SECTION INCLUDES

1. This document specifies Fused Bamboo® Decking made from the renewable resources of 87% Moso Bamboo and 13% Phenolic Resin, a product manufactured based on Dasso's Patent US: 8,709,578 B2
2. Composite Soffit and Wainscoting

1.2 RELATED SECTIONS

- a) Section 00 31 25.26 - Existing Wood, Plastics, and Composites Information
- b) Section 06 81 00 - Composite Railings
- c) Section 06-11 00 - Wood Framing
- d) Section 07 10 00 - Damp proofing and Waterproofing
- e) Section 31 10 00 - Site Cleaning
- f) Section 07 27 00 - Air Barriers
- g) Section 07 62 00 - Sheet Metal Flashing and Trim
- h) Section 07 90 00 - Joint Protection.

Include all division 01 Sections containing LEED® Requirements

1.3 REFERENCES

ASTM International

- a. ASTM E 84-12 - Standard Test Method for Surface Burning Characteristics of Building Materials.
- b. ASTM D 1037-2006a - Standard Test Methods for Evaluating Properties of Wood-Based Fiber and Particle Panel Materials.
- c. ASTM D 1413-2007e1 - Standard Test Method for Wood Preservatives by Laboratory Soil Block Cultures.
- d. ASTM F 1679-04 - Standard Test Method for Using a Variable Incidence Tribometer (VIT)
- e. ASTM D 2395-2002 - Standard Test Methods for Density and Specific Gravity (Relative Density) of Wood and Wood-Based Materials.

Additional test methods:

- a. AWPA E1-09 - Standard Method for Laboratory Evaluation to Determine Resistance to Subterranean Termites.
- b. AWPA E10-11 -Standard Method of Testing Wood Preservatives by Laboratory Soil Block Cultures
- c. ANSI / NFPA # 225: "Standard Method of Test for Surface Burning Characteristics of Building Materials"

US Green Building Council's Leadership in Energy and Environmental Design Green Building Rating System® (LEED)

1.4 SUBMITTALS

Submit under provisions of Section 01 30 00 - Administrative Requirements.

- a. Product Data: Indicate sizes, profile, surface style and performance characteristics.

- b. Samples: For each product specified, one sample, minimum size of 3.5" inches long, representing actual product, color, and finish.

1.5 DELIVERY, STORAGE, AND HANDLING

Storage and Handling:

1. Never dump DassoXTR materials when unloading
2. Store on a flat surface and cover with non-translucent material. If possible products in manufacturer's unopened packaging until ready for installation.
3. When carrying DassoXTR planks, carry on edge for better support
4. Refer to installation instructions for additional guidelines on each product

1.6 WARRANTY

- a. Warranty: Limited Warranty against rot, decay and termites damage for a period of 20 years beginning from the date of purchase under normal conditions of the use and exposure.

1.7 QUALITY ASSURANCE

- a. Manufacturer Qualifications: Company specializing in manufacturing the products specified in this section with minimum ten years of code compliant products for 10 years.
- b. Material Disclosures Required: Health Product Declaration - MSDS sheets requires with submittal package.
- c. Installer Qualifications: Minimum 2 years' experience installing similar products.
- d. Mock-Up: Provide a mock-up for evaluation of surface preparation techniques and application workmanship.
- e. Finish areas designated by Architect.
- f. Do not proceed with remaining work until workmanship is approved by Architect.
- g. Refinish mock-up area as required to produce acceptable work.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

Contract Documents are basis of design, products by:
Manufacturer: Dasso Group
Address: 6060 Boat Rock Blvd SW, Atlanta, GA 30336
Tel: +1-404-691-6872
eMail: info@dassoXTR.com

website: dassoXTR.com

Species: Moso Bamboo (*Phyllostachys pubescens*)

Substitutions: Not permitted.

Any requests for substitutions will be considered in accordance with provisions of Section 01 60 00, 2 weeks prior to project bidding.

2.2 APPLICATIONS/SCOPE

Fused Bamboo Materials:

Material Description: Stranded Reconstructed Bamboo Plank consist of 87% thermalized bamboo fiber and 13% Phenolic Resin, fused together under high temperature and heat with the following physical properties:

- a. XTR-SOF12-100TG-PP: Classic 4" Soffit & Wainscoting Shiplap Fused Bamboo DassoXTR Fused Bamboo Thickness: 1/2" Width: 3 30/32" Length: 72"
- b. Termites Resistance AWPA E1-09: Rating 8
- c. Decay Resistance AWPA E10-12: Class A
- d. Hardness when tested in accordance with ASTM D-143: 3,820 lb
- e. Water Absorption with tested in accordance with ASTM D-1037: %vol.<1.35%, %mass<1.29%
- f. Flame Spread Index when tested in accordance With ASTM E-84: Class A (10)
- g. Smoke Development when tested in accordance with ASTM E-84: Class A (40)
- h. Flame Spread Rating CAN/ULC S102-10: 20
- i. Smoke Developed Classification CAN/ULC S102-10: 25
- j. Spread of Flame Test CAN/ULC-S107-10: Class A
- k. Intermittent Flames Exposure Test CAN/ULC-S107-10: Class A

2.3 LEED INFORMATION

Under the LEED version 2009, the use of dassoXTR Fused Bamboo products may contribute following credits for the most applicable rating system – Building Design & Construction (BD+C):

- a) MR Credit 6 – Rapid Renewable Materials
- b) MR Credit 7 – Certified Wood (FSC Certified Product)
- c) IEQ Credit 4.3 – Low Emitting Materials: Flooring System (applies to Porch Flooring)
- d) IEQ Credit 4.4 – Low Emitting Materials: Composite Wood (applies to all Fused Bamboo)

Under the LEED version 4, the use of dassoXTR Fused Bamboo products may contribute following credits for the most applicable rating system – Building Design & Construction (BD+C):

- a) MR Credit 1 – Building Life Cycle Impact Reduction
- b) MR Credit 2 – Building Product Disclosure and Optimization – Environmental Product Declaration
- c) MR Credit 3 – Building Product Disclosure and Optimization – Sourcing of Raw Materials (FSC Certified Product)
- d) IEQ Credit 2 – Low Emitting Materials

2.4 ACCESSORIES

Fasteners:

- a. Hung on clips which are mounted on-panel or to studs/batten. Use marine-grade stainless steel fasteners designed for fastening to the panel/batten (wood or metal screws to wood or metal).

2.5 FINISH

- a. Face / Bottom Milling: Smooth faces
- b. Pre-Primed with WOCA Oil: <https://www.wocadirect.com/about/>
- c. See company website for finishes and cleaning. Per manufacturers requirements to maintain warranties.
<https://dassoXTR.com/Products/Finishes,SealersandCleaners.aspx?pgId=582>

PART 3 - EXECUTION

3.1 EXECUTION

Examination

- a. Install according to manufactures instructions.
- b. Installer Qualifications: Minimum 2 years experience installing similar products.
- c. Cut, drill and rout using carbide tipped blades.
- d. Cut ends square.
- e. CORROSION INFORMATION
For applications exposed to salt air, near large bodies of water, swimming pools or other areas where corrosion is more likely to occur, always use Grade 316 stainless steel screws.

3.2 CLEANING

- a. Clean surfaces regularly with recommended cleaner from Woca, Penofin or Messmers, depending on which coating materials were used to recoat your decking.
- b. Power wash with “fan tipped” nozzle in the direction of the grain of the planks with a maximum pressure of 1500 psi.
- c. Provide owner three copies of cleaning and maintenance instructions.

3.3 PROTECTION

- a. Protect products until project is complete.
- b. Touch-up or repair as needed before substantial completion.

END OF SECTION